

# LEXAN<sup>TM</sup> MARGARD<sup>TM</sup> MR10 SHEET

# PRODUCT DATASHEET

## **DESCRIPTION**

Mar/UV-resistant LEXAN<sup>TM</sup> MARGARD<sup>TM</sup> MR10 sheet combines the impact strength of LEXAN polycarbonate sheet with a proprietary abrasion/UV resistant surface that approaches glass in performance. LEXAN MARGARD MR10 Sheet with MARGARD coating backed by a ten-year limited warranty against yellowing, abrasion resistance, breakage, loss of light transmission, and coating failure.) LEXAN MARGARD MR10 sheet's unique coating is graffiti resistant enabling restoration to a like-new condition. In addition, LEXAN MARGARD MR10 sheet offers improved resistance to weathering as well as forced-entry protection. It is an excellent candidate for use in stores, public buildings, schools, bus shelters and other high traffic areas. LEXAN MARGARD MR10 sheet is for transparent applications only. Because of its high mar-resistant surface, paint, adhesives and other materials will not adhere to its surface. The coating is applied to both sides, therefore helps eliminate second-surface decoration. Also due to its mar-resistant coating, LEXAN MARGARD MR10 sheet cannot be cold-formed.

# TYPICAL PROPERTY VALUES◆

PROPERTY	TEST METHOD	UNITS	VALUE	
Physical		·		
Specific Gravity (color dependent)	ASTM D792	-	1.20	
Chemical Resistance	ANSI Z26.1	-	Passes#	
Mechanical				
Tensile Strength, Ultimate	ASTM D638	psi	9,500	
Flexural Strength	ASTM D790	psi	13,500	
Flexural Endurance @ 1,800 Cycles/Min,				
73°F, 50% RH	ASTM D671	psi	1,000	
Compressive Strength	ASTM D696	psi	12,500	
Modulus of Elasticity	ASTM D638	psi	345,000	
Drop Ball Impact Strength‡	SABIC Test	ft-lbs		
@ 73°F			>200	
@ 32°F			>200	
@ 0°F			>200	
Thermal				
Coefficient of Thermal Expansion	ASTM D696	in/in/°F	3.75 ×10 <sup>-5</sup>	
Heat Deflection Temperature @ 264 psi	ASTM D648	°F	270	
Flammability				
Horizontal Burn (Flame Spread)	ASTM D635	in		
AEB			<1	
Ignition Temperature	ASTM D1929	°F		
Flash			873	
Self			1,076	

- These typical values are not intended for specification purposes. If minimum certifiable properties are required please contact your local SABIC representative.
- ‡ 5-lb steel ball dropped from a height of 40 feet
- ™ Trademarks of SABIC.
- ${\hbox{\it E}} \quad \hbox{\it Request details of limited ten-year warranty plus cleaning and maintenance instructions}.$
- ${\tt \#\ Gasoline\ and\ kerosene\ -\ no\ tackiness,\ crazing\ or\ loss\ of\ transparency\ for\ a\ minimum\ of\ 48\ hours.}$

UL File Number: E121562

# ABRASION RESISTANCE COMPARISON

LEXAN™ MARGARD™ MR10 sheet exhibits significantly less hazing than uncoated polycarbonate sheet as shown in the abrasion resistance chart.

			% HAZE	
	Test Method	Uncoated Polycarbonate	LEXAN MR10 Sheet	Glass
TABER ABRASION	ASTM	35.0	1-3	0.5
100 CYCLES CS	D1044			
10F	Z26.1			

<sup>‡</sup> The Taber Abrader test measures the percent of change in haze that results from the grinding action of two abrasive impregnated wheels on the test samples. A constant load of 500 grams is maintained as the samples rotate on a turntable for a predetermined number of revolutions.


# **IMPACT RESISTANCE**

¼" LEXAN™ MARGARD™ MR10 sheet

¼" Acrylic

¼" Tempered Glass

1/4" Laminated Glass



Measured in foot-pounds

## **OPTICAL**

	Gauge	Test Method	Typical Value
Light Transmission	0.118	ASTM D1003	88%
Light Transmission	0.236	ASTM D1003	85%
Light Transmission	0.500	ASTM D1003	80%

#### CODE COMPLIANCE

LEXAN MARGARD MR10 sheet meets the requirements of all major model building codes

• Model Building Code Organizations The Approved Light Transmitting Plastics requirements set by the three

major Model Building Code organizations (BOCA, ICBO, and SBCCI) and Dade County. LEXAN MARGARD MR10 sheet meets the highest rating -

Class CC1 Approved Plastic.

• Underwriters Laboratories LEXAN MARGARD MR10 sheet is listed as a Burglary-Resisting Glazing

Material according to UL Standard 972.

• CPSC: 16 CFR 1201, I, II LEXAN MARGARD MR10 sheet complies with the Consumer Product

Safety Commission's Safety Standard for architectural glazing materials

for both Category I and Category II applications.

# **CONTACT US:**

#### Middle East and Africa

SABIC Global Headquarters PO Box 5101 Riyadh 11422 Saudi Arabia T +966 (0) 1 225 8000 F +966 (0) 1 225 9000 E info@sabic.com

# Email

sfs.info@sabic.com

#### Americas

SABIC Functional Forms 2500 City West Boulevard Suite 100, Houston, TX 77042 USA Toll-free (800) 323 3783 F (888) 443 2033 E spinside.sales@sabic.com

#### Europe

Functional Forms Plasticslaan 1 4612 PX Bergen op Zoom The Netherlands T +31 (0)164 293678 F +31 (0)164 293272 E sfs.info@sabic.com

## Asia Pacific

Functional Forms 2550 Xiupu Road Pudong 201319 Shanghai China T +86 21 2037 8188 F +86 21 2037 8288 E sfs.info@sabic.com

DISCLAIMER: THE MATERIALS, PRODUCTS AND SERVICES OF SAUDI BASIC INDUSTRIES CORPORATION (SABIC) OR ITS SUBSIDIARIES OR AFFILIATES ("SELLER") ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE UPON REQUEST. INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS DOCUMENT ARE GIVEN IN GOOD FAITH. HOWEVER, SELLER MAKES NO EXPRESS OR IMPLIED REPRESENTATION, WARRANTY OR GUARANTEE (i) THAT ANY RESULTS DESCRIBED IN THIS DOCUMENT WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN OR APPLICATION INCORPORATING SELLER'S MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS. UNLESS OTHERWISE PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS DESCRIBED IN THIS DOCUMENT. Each user is responsible for making its own determination as to the suitability of Seller's materials, products, services or recommendations for the user's particular use through appropriate end-use and other testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed by Seller. Statements by Seller concerning a possible use of any material, product, service or design do not, are not intended to, and should not be construed to grant any license under any patent or other intellectual property right of Seller or as a recommendation for the use of any material, product, service or design to other intellectual property right of Seller or as a recommendation for the use of any material, product, service or design in a manner that infringes any patent or other intellectual property right of Seller or as a recommendation for the use of any material, product, service or design in a manner that infringes any patent or other intellectual property right.

SABIC and brands marked with  $^{\text{IM}}$  are trademarks of SABIC or its subsidiaries or affiliates. © 2018 Saudi Basic Industries Corporation (SABIC). All Rights Reserved.

 $^\dagger Any$  brands, products or services of other companies referenced in this document are the trademarks, service marks and/or trade names of their respective holders.

www.sabic.com/sfs

